



Zawór kulowy C 126-I, ręczny

"samopływająca" kula, ciśnienie znamionowe PN 10
uszczelka kuli NBR lub FPM

ball valve C 126-I, manual valves

safefloat ball, pressure rating PN 10
ball seat NBR or FPM

Wielkość DN 25 - DN 100

sizes

d (mm)	32	40	50	63	75	90	110
DN (mm)	25	32	40	50	65	80	100
DN (Zoll / inch)	1	1 1/4	1 1/2	2	2 1/2	3	4

Wymiary
dimensions

dk	24,0	24,0	40,0	50,0	64,0	74,0	83,0
A	150,0	150,0	250,0	250,0	250,0	350,0	350,0
D1	83,0	83,0	132,0	132,0	151,0	178,0	200,0
H	143,0	143,0	180,0	180,0	187,0	200,0	214,0
h	51,0	51,0	76,0	76,0	85,0	99,0	110,0
L1	325,0	400,0	430,0	440,0	465,0	495,0	540,0
M ¹⁾	M 8	M 8	M 8	M 8	M 8	M 8	M 10
s	3,0	3,7	4,6	5,8	6,9	8,2	10,0
t	76,0	100,0	100,0	100,0	105,0	110,0	115,0
w	52,0	52,0	84,0	84,0	95,0	118,0	127,0

Wielkość DN 100 - DN 150

sizes

d (mm)				125	160	180
DN (mm)				100	150	150
DN (Zoll / inch)				4	6	6

Wymiary
dimensions

dk				83,0	120,0	120,0
A				350,0	450,0	450,0
D1				200,0	278,0	278,0
H				214,0	253,0	253,0
h				110,0	149,0	149,0
L1				550,0	730,0	730,0
M ¹⁾				M 10	M 12	M 12
s				11,4	14,6	16,4
t				125,0	160,0	160,0
w				127,0	160,0	160,0

1) Standard bez części metalowych 1) standard without metal inserts